

AHSC-140P









220V~60Hz, 3 Ph
Simple design, duct connection type!
Optimized design for external environment!

Airrex heat pump operates in air temperatures from 65° to 113°F for cool mode, dehumidification from 86.16 to 124.8 (gal/day), and 1° to 81°F for heat model. AHSC-140P utilizes eco-friendly 410A refrigerant.

Airrex AHSC-140P may require a fresh air supply for proper operation. Includes 2" pleated paper filters. Thermostatically protected compressor includes high and low pressure warnings. Moves easily on swivel casters (4" locking). 145,000 BTU cooling and 100,000 BTU heating features 16" supply duct and 16" return duct and 20" diameter rear warm air discharge. 1 year warranty and 3 years on compressor.



Strong Points

- 
 Large space air conditioner
- 
 Automatic temperature control
- 
 Concentrated cooling
- 
 Movable & Lockable
- 
 Optimization of cooling capacity
- 
 Automatic
- 
 Time Setting
- 
 Certification



Performance improvements
 Large capacity FAN to outdoor unit gets optimised performance



Outdoor installation
 Cool and heat air circulation system for indoor and outdoor use.



Simple structure
 User friendly, optimized, Easy to use, Easy after-sales service.



Digital Controller
 OFF timer/Temperature control/Remote control
 Self-diagnosis function



Built-in exhaust fan
 Exhaust fan design.



Portable air conditioner
 Urethane wheels with convenient lockable wheels