

# AHSC-60

**460V~60Hz, 3 Ph**

**Simple design, duct connection type!**

**Optimized design for external environment!**

Airrex heat pump operate in the air temperatures from 65° to 113°F for cool mode, dehumidification from 52.8 to 76.56 (gal/day) and 50° to 81°F for heat model. These heat pumps utilize eco-friendly 410A refrigerant.

Airrex heat pump may require a fresh air supply for proper operation. Includes removable, washable air filters for easy maintenance. Thermostatically protected compressor includes high and low pressure warnings. Moves easily on swivel casters (8" locking). 60,000 BTU cooling and 60,000 BTU heating features 12" supply duct and 16" return duct and 26" diameter top exhaust, with optional 20" reducer.

1 year warranty and 3 years on compressor.



## Strong Points



Large space air conditioner



Automatic temperature control



Concentrated cooling



Movable & Lockable



Optimization of cooling capacity



Automatic



Time Setting



Certification



### Performance improvements

Large capacity FAN to outdoor unit gets optimised performance



### Outdoor installation

Cool and heat air circulation system for indoor and outdoor use.



### Simple structure

User friendly, optimized, Easy to use, Easy after-sales service.



### Digital Controller

OFF timer/Temperature control/Remote control Self-diagnosis function



### Built-in exhaust fan

Exhaust fan design.



### Portable air conditioner

Urethane wheels with convenient lockable wheels