## **HSC-24** P

## PORTABLE AIR CONDITIONER

**Cool Solutions by Airrex!** 

Approved technology with 37 years experience in the market! Airrex Spot Cooler 2-Ton

Airrex spot coolers operate in air temperatures from 61°F to 115°F. These air conditioners utilize eco-friendly R-410A refrigerant.

Airrex spot cooler air conditioners may require a fresh air supply for proper operation. Includes removable, washable air filters for easy maintenance. Thermostatically protected compressor includes high and low pressure warnings. Moves easily on four swivel casters (2 locking). 23,500 BTU Cooling feature two 5" diameter front cold air discharge and 16" flared diameter top warm air discharge.

Optional Warm Air Duct includes ducting and a 2' x 2' ceiling flange for warm air exhausting.

ETL listed. Optional Condensate Pump that plugs directly into the portable air conditioner.

1 year warranty and 3 years on compressor.

## Strong Points





















Hot Air Exhaust

Automatic Fan Speed Controller Operating Range: Up to 115'F



Twist & Lock

(2) 5"x14" Easy to disassemble & store



Mobility

(4) 4" Swivel Casters (2) Locking Casters



Condensate Tank

5 Gallon Tank Auto Shut off




Spot Cooling

Directed Cooling 13,600Btu/h



Digital Controls

Programmable Timer Temperature Range: 61°F to 86°F High/Low Fan Speed / Auto Restart



**LCDI Protection** 

LCDI Recessed Power Cords Standard 115 Volt Power ETL Certified



Applications

Indoor or Outdoor Cooling Drying

